Bruce®



PHOTO: Seaside Calm, Oak, CB4260LG

DUNDEE® | SOLID HARDWOOD

Showcasing the Beauty of Oak

- Made from select and premium grade Appalachian Oak
- Delivers greater stability and color consistency, with fewer streaks and knots
- Beautiful colors accentuate the natural grain pattern and character of oak
- Features Dura-Luster® Plus coating, a multi-layer finish and highest level of protection

50-YEAR LIMITED RESIDENTIAL WARRANTY | 10-YEAR LIMITED COMMERCIAL WARRANTY

ALL BRUCE SOLID HARDWOOD FLOORS ARE PROUDLY MADE IN THE USA.

LASTING STRENGTH

Bruce hardwood flooring offers a Limited Lifetime Warranty against structural defects for as long as you own your hardwood floor.**

Scan to learn more about Dundee®

floor score

CERTIFIED BY SCS Global Services

APPALACHIAN HARDWOOD · VERIFIED SUSTAINABLE · AHMI

DUNDEE® | SOLID HARDWOOD

OAK



Inviting Warmth
3-1/4" **CB3230LG**
4" **CB4230LG**
5" **CB5230LG**



Natural
3-1/4" **CB3220LG**
4" **CB4220LG**
5" **CB5220LG**



First Frost
3-1/4" **CB3265LG**
4" **CB4265LG**
5" **CB5265LG**



Seaside Calm
3-1/4" **CB3260LG**
4" **CB4260LG**



Equestrian Woods
3-1/4" **CB3225LG**
4" **CB4225LG**
5" **CB5225LG**

DUNDEE SOLID							
SPECIES	Oak	THICKNESS	3/4"	PLANK LENGTH(S)	8.25"-84"	TEXTURE	Smooth
WIDTHS	3-1/4", 4", 5"	GLOSS	Low	FINISH	Dura-Luster® Plus Urethane		
EDGE DETAIL	Micro-beveled edges and square ends			BOARD-TO-BOARD VARIATION	Most		
INSTALLATION	Nail, Staple with Glue Assist* On / Above Ground Level			WARRANTY	50-Year Limited Residential, 10-Year Limited Commercial, Lifetime Structural Warranty**		
SQ FT PER CARTON	3-1/4" - 22, 4" - 18.5, 5" - 23.5	CARTONS PER PALLET	3-1/4" - 32, 4" - 50, 5" - 40	SQ FT PER PALLET	3-1/4" - 704, 4" - 925, 5" - 940	PALLETS PER TRUCK/CONTAINER	3-1/4" - 21, 4" & 5" - 16

	Quarter Round	T-Molding	Reducer Strip	Threshold	Stairnose
Natural	TQ0RK642L	TM0RK642L	TR9RK642L	TH0RK642L	TS9RK642L
Equestrian Woods	TQ0RK643L	TM0RK643L	TR9RK643L	TH0RK643L	TS9RK643L
Inviting Warmth	TQ0RK644L	TM0RK644L	TR9RK644L	TH0RK644L	TS9RK644L
Seaside Calm	TQ0RK645L	TM0RK645L	TR9RK645L	TH0RK645L	TS9RK645L
First Frost	TQ0RK646L	TM0RK646L	TR9RK646L	TH0RK646L	TS9RK646L

*For widths greater than 3-1/4", glue assist is required. See installation instructions for additional details. **See limited warranty for additional details, including use of AHF Products recommended adhesive for enhanced warranty coverage.

WB-1350-926 FloorScore® is a trademark of the Resilient Floor Covering Institute. All other trademarks owned by AHF, LLC. © 2026 AHF, LLC.
NOTE: Due to printing limitations, colors pictured cannot be guaranteed to match actual flooring material.